

Key Features

- X-scale PXA255 400Mhz 32 bits RISC Processor
- 64/128 MB SDRAM and 64MB Flash ROM
- One CF-II and SD expansion slot
- Support USB1.1 Client and Host
- Integrated barcode scanner (laser)
- Wireless Communication Ready (802.11b or Blue-Tooth)
- Alphanumeric Keyboard Build-in



Specifications

Processor

- X-scale PXA255 400Mhz 32 bits RISC CPU

Chipset

- Intel Cotulla embedded chipset
- Media-Q MQ1188 Graphic, SD and USB host Controller
- Wolfson WM9705 AC'97 codec with Touch screen controller

Memory

- 64MB (M-System) Flash ROM
- 64/128MB SDRAM

Display

- Support 240 X 320 TFT 256K Color LCD
- Transflective type TFT LCD with back light
- Support 4-wire resistance type touch panel

Audio

- One mono speaker
- 2.5mm DIA stereo earphone jack with Microphone input.

USB Function

- Support USB 1.1 Compliant Function
- Support USB 1.1 Compliant Host in 100mA
- USB interface will support from cradle USB connector or external USB cable

Barcode

- Laser Engine

Infrared Port

- One IrDA 1.2 compliant SIR port support 20cm ~ 30cm distance

Expansion Slot

- One Compact Flash Type-II slot (support 3.3V)
- One SD Card slot (support SDIO)

Power system

- Build in 1800mAh Li-Polymer removable battery (10 operation & 100 standby hours in 64MB DRAM and 64 ROM module)
- 25 mAh rechargeable backup battery
- One adapter with 100~240Vac, 50/60Hz
- AC input and 5V/2A DC output
- One DC-IN jack

Button

- One Power/Front light on/off button
- 4-way navigation button
- 2 Scanner Enable Keys
- SW Reset input button
- **16 + 1** alphanumeric keyboard

LED

- One two-color LED for Alarm notification and charger indicator
- One two-color LED for scanner indicator

Cradle

- Support USB client and Host
- Support 2nd battery charge
- Built-in DC-IN jack
- One Charger LED

Power Management

- Support for Xscale application modes including: Turbo Mode, Normal Mode, Idle Mode and Sleep Mode
- Peripheral power – On/Off controllable via software

RADIO Module

- 802.11b or Blue-Tooth (Class II)

Dimensions and Weight

- 78 mm (W) x 168mm(L) x 33mm(H)
- Weight: 350g

Software

- Microsoft WinCE .NET 4.1/4.2
- IE, InBox, Async..etc.
- SW update from CF

Environmental

- Operating Temperature: -10°C~50 °C
- Storage Temperature: -20 °C ~60 °C
- IP54 Standard

- 4 ft (1.2m) drop to concrete

Peripherals and Accessories

- Pistol Grip
- Hand-Strap
- CDMA Module



Key Features

- **PC Communication**
- **Battery Management**
- **USB Host and Client**
- **RS-232**
- **Ethernet Module Ready (optional)**



Specifications

DC Power Jack Input

- DC 5V/2A

2nd Battery Status LED

- No LED: Fully charged
- Amber: Charging
- Flashing: Problem

USB Client Connector

- Connect to PC
- Support USB Client only

USB Host Connector

- Support USB Host
- Support USB device

RS232 D-Sub Connector

- Connect to PC
- Support RS232 full function

Ethernet Module (optional)

- Support 10/100 Mb Ethernet communication
- Connect through USB host connector

2nd Battery Charge Slot

- Support 2nd Battery Charge

Size and Weight

- TDB
- Weight: TDB

Environmental

- Operating Temperature: 0°C ~50 °C
- Storage Temperature: -20 °C ~60 °C
- 75cm drop to concrete

Peripherals and Accessories

- USB Cable (connect to PC)
- RS-232 Cable
- Ethernet Module
- Multi-Docking Station

Switzerland • **OPAL Associates AG** • Motorenstrasse 116 • CH-8620 **Wetzikon** • Telefon +41 (0)44 931 12 22 • Telefax +41 (0)44 931 12 20 • Email info@opal-holding.com • URL <http://www.opal.ch/> • OPAL Associates SA • Avenue des Boveresses 54 • Case postale 29 • CH 1000 **Lausanne 21** • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opal-holding.com • URL <http://www.opalsa.ch/> • Germany • **OPAL Associates GmbH** • Lohnerhofstrasse 2 • D-78467 **Konstanz** Telefon • +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opal-holding.com • URL <http://www.opalgmbh.de/> • OPAL Associates GmbH • Osterholder Allee 2 • 25421 **Pinneberg** • Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email info@opal-holding.com • OPAL Associates GmbH • **München** • Telefon +49 (0)89 12737 556 • Telefax +49 (0)89 12737 557 • Email info@opal-holding.com • OPAL Associates GmbH • **Frankfurt** • Telefon +49 (0)69 8236 6501 • Telefax +49 (0)69 8236 7709 • Email info@opal-holding.com • OPAL Solutions GmbH • Wilhelmstr. 22 • 52428 **Jülich** • Telefon +49 (0)2461 936 770 • Telefax +49(0)2461 936 771 • Email info@opal-holding.com • URL <http://www.opal-solutions.de/> • Austria • **OPAL Associates GesmbH** • Vorarlberger Wirtschaftspark • A-6840 **Göttzis** • Telefon +43 (0) 5523 58833 • Telefax +43 (0)5523 521569 • Email info@opal-holding.com • URL <http://www.opalgmbh.at/> • OPAL Associates GesmbH • Donaufelderstr. 101/2/8 • **1210 Wien** • Telefon +43 (0)1 270 03 13 • Telefax +43(0)1 270 03 15 • Email info@opalgmbh.at

