

Dolphin 7800 Android

Enterprise Digital Assistant (EDA)

Leveraging the modern and user-friendly Google® Android™ operating system packed with Honeywell extras, Honeywell's Dolphin™ 7800 Android™ rugged EDA offers remote device management capabilities, invaluable security features, and access to an ever-expanding array of productivity-enhancing applications available on Google® Play (previously the Android™ Market), creating an enterprise-ready solution with an extended lifecycle and support provided by Honeywell.

For demanding mobile workforce applications that require multiple tasks to be completed in a limited amount of time, the Dolphin 7800 Android™ enables multi-purpose computing, communication, and data collection at desktop-like speed, empowering workers to get the job done.

Mobile workers need compact, lightweight devices that are designed for durability and usability. With a magnesium inner chassis and engineering-grade plastic housings, the field-proven Dolphin 7800 Android™ provides unsurpassed reliability, without the extra bulk that often accompanies industrial-grade mobile computers.

A large, high-resolution, outdoor- and off-axis-viewable screen maximizes productivity and ensures easy viewing of data in virtually any lighting condition. Multiple keypad options allow enterprises to choose the layout that best suits the needs of their mobile workforce. Adaptus™ Imaging Technology 6.0 enables fast scanning of linear and 2D bar codes in various lighting conditions, while an integrated color camera enables seamless image and video capture.

When the benefits derived from consumer operating systems are desired in a lightweight yet reliable mobile computing solution, Honeywell's Dolphin 7800 Android™ rugged EDA delivers the functionality required to protect an enterprise, while maximizing the productivity of its workforce.



Preliminary Specifications
Subject to Change

Features

- **Honeywell Enhanced Android™ Operating System:** Provides enterprise users with superior remote management capabilities; valuable security features; a user-friendly interface; access to a multitude of productivity-enhancing applications through Google® Play; and a long lifecycle that matches that of the traditional Dolphin 7800 offering
- **Lightweight and Compact Design:** Reduces user fatigue by offering all of the functionality needed in an easy-to-carry form factor
- **Superior 3.5" Outdoor-Viewable VGA Display:** Allows mobile workers to seamlessly interact with data in virtually any lighting condition
- **Rugged and Reliable:** Durable construction and sealing deliver reliable operation and maximize worker uptime
- **Fast and Reliable Wireless Connectivity:** Delivers full wireless coverage for applications inside and outside of the four walls, allowing real-time access to critical data
- **Powerful Processor and Network Connections:** Delivers fast business transactions, allowing workers to complete multiple tasks quickly
- **Remote MasterMind™ Ready:** Reduces total cost of ownership by providing a turnkey remote device management solution that easily manages and tracks usage of installed devices
- **Service Made Simple™ Service Plans:** Offers comprehensive, hassle-free protection on the device investment for up to three years after purchase, lowering the total cost of ownership

Dolphin 7800 Android Technical Specifications

| Mechanical | |
|---------------------------------|--|
| Dimensions | Standard Battery: 157 mm x 76 mm x 28 mm (6.2" x 3.0" x 1.1") Extended Battery: 157 mm x 76 mm x 33 mm (6.2" x 3.0" x 1.3") |
| Weight | Standard Battery: 324g (11.4 oz); Extended Battery: 380 g (13.4 oz) |
| Environmental | |
| Operating Temperature | -10° to 50°C (14° to 122°F) |
| Storage Temperature | -20° to 70°C (-13° to 158°F) |
| Humidity | 0 to 95% relative humidity (non-condensing) |
| Drop | Designed to withstand 5' (1.5m) drops to concrete |
| Tumble | Designed to withstand up to 1,600 (1m) tumbles per IEC 60068-2-32 specification |
| ESD | ±15KV Air and ±8KV Contact |
| Environmental Sealing | Independently certified to meet IP64 standards for moisture and particle intrusion |
| System Architecture | |
| Processor | 800MHz TI OMAP |
| Operating System | Google® Android™ version 2.3.4 with Honeywell security and manageability features |
| Memory | 256 MB RAM X 512 MB Flash |
| Display | 8.9 cm (3.5") VGA color, high resolution, full axis viewing, sunlight readable display |
| Touch Panel | Industrial touch panel with 4 wire resistive touch and support for finger touch and stylus |
| Keypad | Standard Keyboards: 30-key numeric and 46-key QWERTY |
| Audio | Speaker, HAC receiver, microphone, vibrator, echo cancellation, Bluetooth® headset support |
| I/O Ports | USB 2.0 |
| Camera | 3.0 mega pixel camera; autofocus; flash LED |
| Sensors | 3-Axis/2g Accelerometer |
| Storage Expansion | User accessible microSD slot (SDHC compatible). Please check with your Honeywell representative for available qualified card options |
| Battery | Standard: Li-ion 3.7 V, 2300 mAh; Extended: Li-ion 3.7 V, 4000 mAh |
| Hours of Operation | Standard/Extended: 6.5 hours/12 hours (decoding and sending data over WLAN every 9 seconds) Extended: 8.5 hours (decoding and sending data over WWAN every 15 seconds, GPS continuously receiving data) |
| Decode Options | Supports the following Adaptus 6.0 imaging scan engines: N5603-SR, N5603-ER |
| Decode Capabilities | Decodes standard 1D and 2D bar code symbologies |
| Development Environment | Honeywell SDK for Google® Android™ version 2.3 |
| HSM Application Software | Honeywell Powertools® and Demos, Remote MasterMind™ for Mobility remote device management |
| Warranty | 1 year factory warranty |
| Wireless Connectivity | |
| WWAN | GSM (Voice and Data): 3.9G–HSPA+ (800/850/1900/1700/2100 MHz), GSM/GPRS/EDGE (850/900/1800/1900 MHz) EDGE (850/900/1800/1900MHz) and EVDO Rev A - 1xRTT/EVDO (800/1900 MHz) |
| WLAN | IEEE 802.11 a/b/g/n; Wi-Fi™ certified |
| WLAN Security | 64/128 bit WEP, WPA/WPA2 PSK (TKIP, AES), WPA/WPA2 Enterprise (EAP-TLS, EAP-TTLS, PEAPv0/MSCHAPv2, PEAPv1/GTC) |
| WPAN | 2.4 GHz (ISM Band) Adaptive Frequency Hopping Bluetooth® v2.1 + EDR; Class II: 10m (33') line of sight |
| GPS | Integrated autonomous GPS receiver with built-in Assisted-GPS (A-GPS) services and software utilities |

Google® and Android™ are trademarks or registered trademarks of Google® Inc.

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance

For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies

Preliminary Specifications
Subject to Change



For more information:

www.honeywellaidc.com

Honeywell Scanning & Mobility

9680 Old Bailes Road

Fort Mill, SC 29707

800.582.4263

www.honeywell.com

Honeywell

7800 Android-DS Rev A 04/12
© 2012 Honeywell International Inc.

